# Plugs (continued)



#### **VON 30 Series**

4mm fully mating connector, shatter-proof, flexible insulated sleeve. The tapering sleeve end also serves as kinking protection for the lead. Solder connection up to maxi-mum cable cross-section of 2.5 mm2. Nickelplated brass contact material. Max. current 30A, contact resistance  $3m\Omega$ , temperature range -25°C to +70°C.



Part No.	Description
VON 30 BK	Plug 4mm solderable 30A 51mm black
VON 30 RD	Plug 4mm solderable 30A 51mm red

Part No.	Ord.No.	
S VON 30 BK	36686	
S VON 30 RD	36687	


# **Adaptors**

### MZS 2 Series



Injection-moulded adapter plug from 2 mm diameter plug to 4 mm diameter socket. This adapter plug enables the use of 4 mm plugs and 2 mm measuring leads. Max. current 6A, contact resistance 6m $\Omega$ , temperature range -20°C to +60°C.





Part No.	Description
MZS 2 BK	Adapter plug 2mm/socket 4mm 6A black
MZS 2 RD	Adapter plug 2mm/socket 4mm 6A red


Part No.	Ord.No.
S MZS 2 BK	36675
S MZS 2 RD	36676

## MZS 4 Series



Injection-moulded adapter plug from 4 mm diameter plug to 2 mm diameter socket. This adapter plug enables the use of 2 mm system plugs and 4 mm system measuring leads. Max. current 6A, contact resistance  $6m\Omega$  a temperature range  $-20^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$ .





Part No.	Description
MZS 4 BK	Adapter plug 4mm/socket 2mm 6A black
MZS 4 RD	Adapter plug 4mm/socket 2mm 6A red

Part No.	Ord.No.	
s MZS 4 BK	36677	
S MZS 4 RD	36678	

# **Plugs**

ECONOMIC

### B 71 Series

Plug 4mm. Screw connection up to maxi-mum cable cross-section of 1,5 mm<sup>2</sup>.



Part No.	Description
B 71 BK	Plug 4mm, screw, black, wire max. 1,5 mm <sup>2</sup>
B 71 BU	Plug 4mm, screw, blue, wire max. 1,5 mm <sup>2</sup>
B 71 GN	Plug 4mm, screw, green, wire max. 1,5 mm <sup>2</sup>
B 71 RD	Plug 4mm, screw, red, wire max. 1,5 mm <sup>2</sup>
B 71 YE	Plug 4mm, screw, yellow, wire max. 1,5 mm <sup>2</sup>

Part No.	Ord.No.	
S B 71 BK	2159	
S B 71 BU	2492	
<b>S</b> B 71 GN	4864	
<b>S</b> B 71 RD	2157	
<b>S</b> B 71 YE	4911	

## BS 819 Series

ECONOMIC

Plug 4mm  $\,$  with socket. Screw connection up to maxi-mum cable cross-section of 1,5  $\,\mathrm{mm^2}.$ 



Part No.	Description
BS 819 BK	Plug 4mm, wire max 1,5mm <sup>2</sup> + plug 4mm, black
BS 819 RD	Plug 4mm, wire max 1,5mm <sup>2</sup> + plug 4mm, red
Part No.	Ord.No.
S BS 819 BK	6159
S BS 819 RD	6158

## IMG 2 Banana Plug Set

ECONOMIC

Plug set 2x red, 2x black.



Fait No.	Description	
IMG 2	Plug set 2x red, 2x black	
Part No.	Ord.No.	
S IMG 2	66675	